

Equiplite™ Europe Halyard-Swivel Installation and data sheet.

Dear Customer,

Thank you for purchasing this Equiplite product(s).

General

Equiplite products employ a proprietary DSK 75 Ultra loop to take the majority of the load in the Halyard Swivels.

-Work Load: Break Load 2 x MWL.

-DSK 75 Dyneema Loop, Marine anodised Hi Tensile Alum Body.

Installation

IMPORTANT PLEASE READ

Swivel Connector

Line size is **noted** on the Swivel label in mm, feed full cover eye splice through centre and secure with the compression pin provided. Hole \emptyset is designed for a spliced ____mm \emptyset line, It is **important** that line fits **tightly** in centre hole. If a strop is used rope must fit tightly in centre hole, if necessary contact Equiplite Europe for the optimum strop design.

Load will be **significantly** reduced if small line diameter is used in fitting and does not fill hole.

1. Make sure hole is rounded and free of burrs and sharp edges.
2. The fittings are coated with a UV polyurethane coating.
This coating should be renewed when it wears, for a long life.

Fittings will last indefinitely if the above is followed.

3. Use Bison Silicon/fibre-Glass paste to extra secure the pin.

Maintenance

- Recoat black UV coating periodically to prevent UV damage for long life.
- After sailing in salt water, cleaning loops with fresh water will avoid extra wear.
- Equiplite products are covered or coated for protection against UV.
- Coated loops should be recoated periodically to extend life span of the loops.
- Loops should be replaced if excessive wear occurs and mating parts should be checked.
- Equiplite provides world wide service for your Equiplite products.

Order coating: service@equiplite.eu

We hope that this data sheet will help you with the easy installation and maintenance of our products.

Best Regards,
Equiplite Europe

