

Matching parts should be rounded, smooth, and with no sharp edges or burrs.

Note: Dyneema loops are coated with an UV coating, recoat when worn for long life. It is recommended that loops should be replaced when worn.

*** IMPORTANT NOTE:** when selecting a top swivel, we recommend adding 20 to 30% to the MWL of the drum for the top swivel. Since the load on the top swivel is increased over the luff MWL by a significant percentage of the sheet load.

Furlers should be sized according to MWL and depends on sail size.

The following table gives a rough guide only;

Code 0	Boat size
3FS	< 9 m.
4FS	8-10 m.
5FS	9-12 m.
6FS	11-16 m.
8FS	14-21 m.
10FS	18-30 m.
12FS	30-up m

All prices are retail prices in Euro.

All data approx and subject to change without notice.

Other sizes available on special order.

Unspecified dims. mm.
Break load approx. 2 x MWL.

Standard Swivels 1:1 | Custom

Matching 2:1

Part	MWL (kg)	Wt 1:1 (g)	Block part	MWL (kg)	Wt 2:1 (g)
1.7 FS	1.700	130	12-30-4 LL	1.700	189
2.6 FS	2.600	160	12-30-4 HL	2.600	224
3.6 FS	3.600	185	12-30-4 HL	3.600	249
4.7 FS	4.700	200	14-40-5 HL	4.700	297
6 FS	6.000	290	16-46-6 HL	6.000	466
8 FS	7.600	450	20-65-8 HL	7.600	835
10 FS	11.000	800	25-78-10 HL	11.000	1.418
12 FS	16.000	1.200	35-95-12 HL	16.000	2.400
14 FS	20.000	1.600	50-125-14 HL	20.000	3.200
18 FS	30.000	2.300	50-150-18 HL	30.000	4.900
22 FS	45.000	3.100	On request	45.000	6.200
40 FS	85.000	On request	On request	85.000	On request