

Note: Matching parts should be rounded, smooth, and with no sharp edges or burrs.

Dyneema loops are coated with an UV coating, recoat when worn for long life. It is recommended that loops should be replaced when worn.

All prices are retail prices in Euro.

All data approx and subject to change without notice.

Other sizes available on special order.

Unspecified dims. mm.
Break load approx. 2 x MWL.

SpB: Spinnaker block | Custom

Part	Sheave Ø	2 X Max Sheets (mm)	Throat (mm)	MWL (kg)	Wt.(g)
74-92-14 HL SpB	92	2 X 26	120	19.000	1.490
64-80-12 HL SpB	80	2 X 22	87	14.000	1.400
64-80-12 LL SpB	80	2 X 22	87	8.000	950
54-74-10 HL SpB	74	2 X 18	80	9.000	600
54-74-10 LL SpB	74	2 X 18	80	5.500	550
46-65-8 HL SpB	65	2 X 16	60	6.000	410
46-65-8 LL SpB	65	2 X 16	60	4.000	410
36-55-6 HL SpB	55	2 X 14	45	4.000	290
36-55-6 LL SpB	55	2 X 14	45	3.000	290
30-46-5 HL SpB	46	2 X 14	37	3.000	175
30-46-5 LL SpB	46	2 X 14	37	2.200	175
25-43-5 HL SpB	43	2 X 12	36	3.000	170
25-43-5 LL SpB	43	2 X 12	36	2.200	170
20-42-4 HL SpB	42	2 X 10	32	2.200	85
20-42-4 LL SpB	42	2 X 10	32	1.500	85

Above HL = High load version employing high load low friction polymer