

### NEW TYPE SINGLE DRUM 2:1 WITH NEW INTEGRATED BLOCK

Note: Matching parts should be rounded, smooth, and with no sharp edges or burrs. Dyneema loops are coated with an UV coating, recoat when worn for long life. It is recommended that loops should be replaced when worn.

#### NEW TYPE Drum 2:1 (2:1 with new integrated block) | Custom

Part	MWL (kg)	Wt. 2:1 (g)	Drum $\varnothing$ (mm)	Length (mm)	Sheave block $\varnothing$ (mm)	Line (mm)
10 FS	11.000	3.900	400	250	98	10
12 FS	16.000	4.900	400	277	98	12
14 FS	20.000	On request	540	330	125	14
18 FS	30.000	On request	540	480	135	16
22 FS	45.000	14.000	540	505	180	18

### FURLING SET FOR ALL LOCK SYSTEMS

#### NEW TYPE Drum 2:1 & Swivel 1:1 Set | Custom

Part	MWL (kg)	Wt. Set 2:1 (g)	Drum $\varnothing$ (mm)
10 FS	11.000	4.700	400
12 FS	16.000	6.100	400
14 FS	20.000	On request	540
18 FS	30.000	On request	540
22 FS	45.000	17.100	540