



Equiplite® EQ 3D | LOCK STROP™ Installation and data sheet.

Dear Customer,

Thank you for purchasing Equiplite®

General

Equiplite® products employ a proprietary SK loop to take the majority of the load in 3D | LOCK STROP

Equiplite® 3D | LOCK STROP™ 360° Splice Technology works at a lower percentage of ultimate tensile strength (UTS), reducing EQ Strop™ stress and fatigue.

Important installation Note (Riggers)

Before the **first sail trial** it's very important to pre-tension | line out the Equiplite® 3D | Lock strop™ 360° between both ends, Halyard and end connector to 30% of the MWL.

- Equiplite® equipment is warranted for 12 months from the date of sale to be free of defective material and workmanship and only if used in accordance with specifications and accepted good practice.
- Connectors should be free to align themselves with the load.

Fittings will last indefinitely if the above is followed.

Maintenance

- Replace the Teflon Tape (Miljordare tape) on time to protect the lifespan of the lashing(s).
- Recoat UV coating periodically to prevent UV damage.
- After sailing in salt water, cleaning loops with fresh water will prolong their lifespan.
- Loops should be replaced if excessive wear occurs and matching parts should be checked.
- Equiplite provides world-wide service for your Equiplite product.

service@equiplite.com

We hope that this data sheet will help you with the easy installation and maintenance of our product.

Best Regards,
Equiplite®