

Note: Matching parts should be rounded, smooth, and with no sharp edges or burrs.

Dyneema loops are coated with an UV coating, recoat when worn for long life. It is recommended that loops should be replaced when worn.

All prices are retail prices in Euro.

All data approx and subject to change without notice.

Other sizes available on special order.

**Unspecified dims. mm.
Break load approx. 2 x MWL.**

Use recommended line size

Part	Line Ø (mm)	Throat (mm)	MWL (kg)	Wt.(g)
35-20NS	35	200	40.000	650
34-18NS	34	200	35.000	410
32-18NS <i>new</i>	32	200	35.000	380
34-16NS	34	180	28.000	370
32-16NS	32	180	28.000	360
30-16NS	30	180	28.000	350
34-14NS	34	150	18.000	320
32-14NS	32	150	18.000	320
30-14NS	30	150	18.000	300
24-14NS <i>new</i>	24	150	18.000	290
20-14NS <i>new</i>	20	150	18.000	255
16-14NS <i>new</i>	16	150	18.000	123
28-12NS	28	120	13.000	285
26-12NS	26	120	13.000	280
24-12NS	24	120	13.000	280
All connectors above are custom built				
20-12NS	20	110	13.000	245
18-10NS	18	100	9.500	123
16-10NS	16	80	9.500	121
14-8 NS	14	70	6.500	72
14-7 NS	14	70	6.000	50
12-6 NS	12	30	4.900	34
10-6 NS	10	30	4.900	32
10-5 NS	10	25	3.000	19
8-5 NS	8	25	3.000	18
8-4 NS	8	20	2.200	8
6-4 NS	6	20	2.200	8
5-3 NS	5	20	1.200	6