

Note: Matching parts should be rounded, smooth, and with no sharp edges or burrs. Dyneema and Polyester webbing are both coated with an UV coating, recoat when worn for long life. It is recommended that webbing should be replaced when worn. **Use High load Hanks for top and bottom connections.**



All prices are retail prices in Euro.
All data approx and subject to change without notice.

Unspecified dims. mm.
Break load approx. 2 x MWL.

SAIL HANK HIGH LOAD | CUSTOM

Part	Inner \varnothing (mm)	Outer \varnothing (mm)	MWL (kg)	Wt.(g)
5H	7,8	20	1.500	3
6H	8	27	2.000	9
8H	11,5	32,5	2.500	15
10H	15,5	43,5	3.500	30
12H	20	58,5	6.000	71
15H	24	66	9.000	103
18H	28	76	14.000	167
20H	32	84	19.000	240

Note: SWL with Dyneema webbing, Hanks delivered without webbing.

NEW: SAIL HANK LOW LOAD | LIGHTWEIGHT | LOW COST | CUSTOM

Moulded hanks designed for sewn on polyester webbing (not supplied).

Part	Webbing (wide x thick) (mm)	Outer \varnothing (mm)	MWL kg)	Wt.(g)
23 HM	15x 1	23	600	2
33 HM	20x 1.4	33	1.000	8
44 HM	25x 1.5	44	1.400	18
57 HM	25x 2	57	2.000	36

Note: MWL with polyester webbing, Hanks delivered without webbing.