

SINGLE DRUM

Note: Matching parts should be rounded, smooth, and with no sharp edges or burrs. Dyneema loops are coated with an UV coating, recoat when worn for long life. It is recommended that loops should be replaced when worn.

Drum: The Assemblies below have the added features of: Quick fit and removable line | Fixed entry & exits | Lockable sheave | Quick connect and disconnect soft loop

Part	MWL (kg)	Wt. (g)	Drum Ø (mm)	Length (mm)	Line (mm)
1.7 FS	1.700	226	90	120	6
2.6 FS	2.600	395	100	120	6
3.6 FS	3.600	473	123	135	8
4.7 FS	4.700	810	156	155	8
6 FS	6.000	810	156	155	8

The Assemblies below have the added features of: Quick fit and removable line | Bearing guided entry & exit | Lockable sheave | Quick connect and disconnect soft loop

Part	MWL (kg)	Wt. (g)	Drum Ø (mm)	Length (mm)	Line (mm)
3.6 FS	3.600	473	123	135	8
4.7 FS	4.700	810	156	155	8
6 FS	6.000	810	156	170	8
8 FS	7.600	1.250	190	205	8
10 FS	11.000	1.750	223	250	10

NEW TYPE Drum 1:1 | Custom

Part	MWL (kg)	Wt. (g)	Drum Ø (mm)	Length (mm)	Line (mm)
10 FS	11.000	3.200	400	240	10
12 FS	16.000	3.900	400	257	12
14 FS	20.000	8.000	540	290	14
18 FS	30.000	On request	540	480	16
22 FS	45.000	On request	540	563	18

DRUM & SWIVEL SET

Note: Matching parts should be rounded, smooth, and with no sharp edges or burrs. Dyneema loops are coated with an UV coating, recoat when worn for long life. It is recommended that loops should be replaced when worn.

Drum 1:1 & Top Swivel 1:1 Set | Custom

Drum 1:1 & Top swivel 2:1 | Custom

Part	MWL (kg)	Wt. Set 1:1 (g)	Block part	Drum Ø (mm)	Wt. Set 2:1 (g)
1.7 FS	1.700	365	12-30-4 LL	90	415
2.6 FS	2.600	555	12-30-4 HL	100	619
3.6 FS*	3.600	658	12-30-4 HL	123	722
4.7 FS*	4.700	1.010	14-40-5 HL	156	1.107
6 FS*	6.000	1.110	16-46-6 HL	156	1.276
8 FS	7.600	1.700	20-65-8 HL	190	2.090
10 FS	11.000	2.550	25-78-10 HL	223	3.168

* Also available with fixed entry & exits.

FURLING SET FOR ALL LOCK SYSTEMS

NEW TYPE Drum 1:1 & Top Swivel 1:1 Set | Custom

Part	MWL (kg)	Wt. Set 1:1 (g)	Drum Ø (mm)
10 FS	11.000	4.000	400
12 FS	16.000	5.100	400
14 FS	20.000	9.600	540
18 FS	30.000	On request	540
22 FS	45.000	On request	540